



## Product Technical Statement

### WOODLAND LIFESTYLE REVIVE FLOORING

Version 2 April 2025

**Designated Building Product:** Class 1.

#### Declaration

Woodland Lifestyle (Woodland) has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022. See **Regulations**.

#### Company Details

Name	Woodland Lifestyle
Role	Importer and Manufacturer
NZBN	9429046834164
Address	3 Wilson Rd, Upper Moutere 7175
Website	<a href="http://www.woodlandlifestyle.com">www.woodlandlifestyle.com</a>
Email	<a href="mailto:hello@woodlandlifestyle.com">hello@woodlandlifestyle.com</a>
Phone	(09) 308 7948

#### Description of Revive flooring

Revive flooring is a multi-layer SPC, rigid luxury vinyl plank comprising of a limestone and vinly composite structural grey core, high-resolution printed decorative film, and a sound-mitigating underlay.

The planks are 228 mm x 1220 mm (w x l) and are 7 mm thick. The planks include a Uniclic® locking system for simple installation. Around the floor perimeter, a bead of silicon ensures that the floor is waterproof whilst still allowing for expansion and contraction.

# Product Technical Statement

## WOODLAND LIFESTYLE REVIVE FLOORING

Version 1 April 2025

### Building code obligations

Code Clauses	Compliance pathway	Evidence
B1 (structure) B1.3.2, B1.3.3 (b, e, j, q)	ALTERNATIVE SOLUTION	SCS Global Services [11/12/2020] ASTM F3261-20 Standard Specification for Resilient Flooring in Modular Format with Rigid Polymeric Core, Regn # SCS-AC-06577.
B2 (durability) B2.3.1(c), B2.3.2 (b)	ALTERNATIVE SOLUTION	Characteristics covered in the specification include: dimensions including dimensional stability, residual indentation, flexibility, resistance to chemicals, resistance to heat, and resistance to light.  NZ does not have a cited standard in respect of any vinyl flooring material.
C3 (fire affecting areas beyond the fire source) C3.4(b)	ACCEPTABLE SOLUTION	AWTA [27/04/2018] ISO 9239-1:2010, Test #16-001903.  Mean critical flux 5.7 kW/m <sup>2</sup> .
D1 (access routes) D1.3.3 (d)	ACCEPTABLE SOLUTION	ISTS [08/03/2023] AS/NZS.4586:2004, Contract # 8006.  Pendulum mean BPN 31.
E3 (internal moisture) E3.3.3 E3.3.5 E3.3.6	ALTERNATIVE SOLUTION	E2/AS1 para 3.1.1(a) recognises that the material PVC (vinyl) is impervious.  NZWTA [01/03/2023] ISO 4760:2022, #1452577.8.  No evidence of water penetration through the joints.
F2 Hazardous Building Materials F2.3.1	ALTERNATIVE SOLUTION	SCS Global Services [22/01/2019], #VMHL1901000799HG.  Total SVHC ≤ 0.1% (w/w).

# Product Technical Statement

## WOODLAND LIFESTYLE REVIVE FLOORING

Version 1 April 2025

### Scope of use and limitations

Scope	Limitation
Building work	<ul style="list-style-type: none"><li>The substrate must have a moisture content of &lt;6 % at the time the floor is laid. For a concrete substrate and where the moisture content is &gt; 6 %, a layer of 6 ml polyethylene may be installed.</li><li>Revive may <u>not</u> be laid over the following substrates:<ul style="list-style-type: none"><li>- Carpet underlay or carpet</li><li>- Cushioned back vinyl</li><li>- Engineered or solid hardwood over concrete</li><li>- Rubber</li><li>- Cork</li><li>- Laminates</li><li>- Free floating floors.</li></ul></li><li>Substrates must not slope more than 25 mm per 1.83 m in any direction.</li><li>Maximum deflection of the substrate must be &lt; 1/360.</li><li>Substrates must be smooth and free of roughness with no changes in elevation. They must be 3.0mm flat in a 2 m radius.</li></ul>
For all building classified uses.	<ul style="list-style-type: none"><li>For commercial and industrial uses, refer to Woodland Lifestyle.</li><li>Revive is only for use in interior situations.</li><li>Revive is not intended for use as a shower flooring.</li><li>Maximum room size must not exceed 10m x 10m without expansion breaks.</li></ul>
For use as a flooring in an access route	<ul style="list-style-type: none"><li>Revive flooring is not suitable for use in an access route where it is likely to become wet.</li></ul>
In connection with underfloor heating.	<ul style="list-style-type: none"><li>The substrate surface must not exceed 29° C.</li></ul>

### Conditions of use

The system must be installed and maintained with all of Woodland Lifestyle requirements.

### Additional information

For all design, installation and maintenance-related information, and for information supporting Woodland Lifestyle claims, refer to [www.woodlandlifestyle.co.nz](http://www.woodlandlifestyle.co.nz)

### Responsible person

In accordance with Regulation 8, as the responsible person, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is, therefore, to the best of my knowledge, correct.

Signed for and on behalf of Woodland Lifestyle:

Moses Hewetson

Moses Hewetson  
GENERAL MANAGER

2 April 2025