



LUXURY VINYL FLOORING

BEAUTIFUL. DURABLE. 100% WATERPROOF.

2000XL LONG PLANK



Product Construction

A FX3 Surface Protectant[™]

Treated with Ultra-Fresh, an advanced polymer finish that provides the ultimate in abrasion resistance and stain repellency. Integrated Ultra-Fresh treatment inhibits the growth of odor and stain causing mold and mildew.

B Clear Vinyl Wear Layer

A transparent vinyl wear layer provides significant durability against scuffs & abrasions.

C ISOCORE Technology®

A highly engineered closed-cell extruded structural grey core. ISOCORE Technology® is 100% waterproof, rigid, light, strong & dimensionally stable.

D Angle Locking Technology

Angle locking technology is profiled on long-edges of planks to facilitate a fast, floating-floor installation.

E High-Resolution Printed Decorative Film

High-resolution printed film delivers the beauty and realism of natural wood with vivid clarity.

B

(c)

D

F Solid Vinyl Top Layer

Multiple layers of solid virgin vinyl enhances durability and facilitates authentic embossing.

G DROPLOCK 100[™] Technology

End joints utilize DROPLOCK 100[™] Technology to facilitate a folddown locking connection that dramatically expedites installation speed and aligns the top surfaces of adjoining planks.

(H) Integral Sound Mitigating Underlayment Treated with Ultra-Fresh

(E)

G

E

Ð

A pre-attached underlayment that minimizes both reflected and transmitted sound, is shock-absorbing, provides warmth and comfort underfoot and helps further conceal subfloor imperfections. Ultra-Fresh treatment inhibits the growth of odor and stain causing mold and mildew.



FEATURE	BENEFIT
REVOLUTIONARY ISOCORE TECHNOLOGY®	 100% Waterproof Strong, rigid and dimensionally stable Installs over most existing hard surfaces, including ceramic tile No telegraphing from minor subfloor imperfections No acclimation required in residential applications Superior accoustics
ULTRA-FRESH FRESHNESS PROTECTION	 Inhibits the growth of surface mold and mildew on all treated surfaces Eliminates odors and stains associated with the growth of mold and mildew
DROPLOCK 100 [™] LOCKING SYSTEMS	 Fast, easy, glueless floating installation Superior locking technology for a tight fit Suitable for use with subfloor radiant heat
TOUGH, TRANSPARENT WEAR LAYER WITH FX ³ SURFACE PROTECTANT	 The ultimate in abrasion protection Superior stain repellency for easy clean-up Integrated Ultra-Fresh inhibits the growth of odor and stain causing mold and mildew
AUTHENTIC LOOKS AND TEXTURES	 Natural wood beauty with the superior performance of LVT Realistic embossing indistinguishable from real hardwood High definition visuals and rich surface textures deliver a natural appearance at a fraction of the cost of real hardwood floors
LOW MAINTENANCE	 No waxing or surface treatments required Sweep, dust mop, or vacuum daily Use walk-off mats at outside entrances
DESIGN VERSATILITY	 Combines the beauty of hardwood, the durability of LVT, and the ease of angle-lock installation Recommended for Retail, Hospitality, Multi-Family, Corporate, Educational, and Residential Suitable for traditional wet areas including baths, laundry rooms, kitchens, and below-grade (basement) applications
PREMIUM ATTACHED FOAM UNDERLAYMENT	 Improves sound absorption for quieter environment Provides warmth and comfort under foot Reduces foot fatigue and impact stress on joints






























• Some patterns in this series are HIGH CONTRAST DESIGNS.

2000XL LONG PLANK



Specifications

Size:	220 x 1510 mm plank size		
Gauge:	8.5 mm		
Coverage:	8 pieces/carton = 2.66sq.m		
Wear Layer:	0.508 mm		
Edge:	Micro-Bevel		
Finish:	Natural Timber		
Warranty:	Lifetime Residential		
	15 Year Commercial Warranty*		

*Limited Warranty - see www.woodlandlifestyle.com for full warranty details.








Moulding Profiles

All Mouldings Length: 2400mm

All measurements are approximate. * Installs with included trim track.



2000XL LONG PLANK

Sound Ratings

Metroflor has a comprehensive sound rating program. Engage Genesis is tested in the two most common ceiling assemblies to provide you with accurate STC and IIC ratings.

MAKE SURE YOU'RE COMPARING APPLES WITH APPLES!

STANDARD	DESCRIPTION	ASSEMBLY	IBC REQUIREMENTS	RESULTS
ASTM E90 & ASTM E413	Airborne Sound Transmission Loss of Building Partitions and Elements (STC / Sound Transmission Class)	150mm Concrete Slab	STC≥50	STC 51 (Surpasses Requirements)
		150mm Concrete Slab + Drop-Ceiling	STC≥50	STC 62 (Surpasses Requirements)
ASTM E492 & ASTM E989	Impact Sound Transmission Through Floor-Ceiling Assemblies	150mm Concrete Slab	IIC≥50	IIC 53 (Surpasses Requirements)
	(IIC / Impact Insulation Class)	150mm Concrete Slab + Drop-Ceiling	IIC ≥ 50	IIC 69 (Surpasses Requirements)
ASTM E2179 & ASTM E989	Effectiveness of Floor Coverings in Reducing Impact Sound Transmission (ΔIIC / ΔImpact Insulation Class)	150mm Slab	N/A	ΔIIC 24

PRO TIP

Be sure and specify the ceiling assembly you require for your flooring project from your supplier and ask your supplier the ceiling assembly used to achieve the ratings if it isn't specified on their documentation. Better yet, just ask your flooring supplier for the "Delta IIC" that provides the IIC rating for just the





LINK TO METROFLOR SOUND REPORTS





OUR QUALITY STANDARDS

Metroflor Engage Genesis® delivers high style, durability and easy maintenance. It is manufactured using the latest technology and to international standards and quality assurance based on ISO 14001 and ISO 9001.

USGBC Member he U.S. Green Building Council® is ommitted to a prosperous and sustainable uture for our nation through cost-efficient nd energy-saving green buildings.



Ultra-Fresh is a registered trademark of Thomson Research Associates Inc.



FLOORSCORE® CERTIFIED... SO YOU CAN BREATHE EASIER!

FloorScore® is a certification program established by the Resilient Floor Covering Institute (RFCI) for hard surface flooring and flooring adhesive products that meet strict indoor air quality (IAQ) requirements. Products bearing the FloorScore® label meet the indoor air quality emissions criteria of LEED, CHPS, the Green Guide for Health Care, and are recognized by a long list of healthy building programs.





Proudly supplied and distributed by:

WOODLAND LIFESTYLE

Phone **(09) 308 7948** Email **hello@woodlandlifestyle.com** 3 Wilson Road, Upper Moutere 7175, New Zealand Engage Genesis® with Isocore Technology® is a patent-pending product from Metroflor Corporation.

Swatch images within this brochure are shown for reference only and may not reflect final product color match.

© 2021 Metroflor Corporation May 2021