
HERRINGBONE #

COMMERCIAL

Featuring SISOCORE Technology®



Microscopic ceramic particle suspended in a UV cured urethane coating for superior wear & stain resistance and easy care & maintenance. Ultra-FreshTM treatment inhibits the growth of odour and stain causing mould and mildew.

Clear Vinyl Wear Layer – 0.55mm

Transparent vinyl wear layer provides significant durability against scuffs and abrasions in

commercial applications.

- High-Resolution Printed Decorative Film
 High resolution printed film with natural wood grains selected for the herringbone pattern.
- Solid Vinyl Top Layer 2.0mm

 Multiple layers of solid virgin vinyl enhances durability, provides resistance against dents & chips, facilitates authentic embossing and improved comfort under foot.

E ISOCORE Technology[™] – 5.0mm
A highly-engineered, structural, grey core made from extruded, closed-cell vinyl, ISOCORE Technology[™] is 100% waterproof, rigid, light, strong, and dimensionally stable.

Easy Drop & Lock Installation
Innovative DropLock 400 installation system enables fast and easy to install in either single or double herringbone.

G Integrated Sound Mitigating Underlay
An integrated 1mm underlay reduces both reflected and transmitted sound, provides warmth and comfort underfoot and helps conceal substrate imperfections. Ultra-Fresh™ treated.

