Woodland Lifestyle Oasis & Oasis Wide Laminate Flooring PRODUCT TECHNICAL STATEMENT

Version 1.2. September 2023



Designated Building Product: Class 1.

Declaration

Woodland Lifestyle (Woodland) has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022. See **Regulations**.

Company Details

Name	Woodland Lifestyle		
Role	Supplier		
NZBN	9429046834164		
Address	3 Wilson Rd, Upper Moutere 7175		
Website	www.woodlandlifestyle.com		
Email	hello@woodlandlifestyle.com		
Phone	(09) 308 7948		

Manufacturer Details

866.843.8453	UNILIN bvba - Division Flooring	
Address	Ooigemstraat 3, B-8710 Wielsbeke	
	Belgium	
Email	https://www.unilintechnologies.com/en/technologies/flooring	
Phone	T +32 56 62 80 81	

Description of Oasis & Oasis Wide Laminate Flooring

Oasis and Oasis Wide laminate flooring (Oasis) is a direct pressure laminate flooring comprising a high density fibreboard (HDF) core which is then coated with a melamine resin that is reinforced with aluminium oxide.

It is intended for interior use including where exposed to watersplash but is not intended for use in areas of high humidity (e.g. saunas) or wet areas (e.g. shower enclosures).

The boards are 1261 mm in length, 8 mm thick and either 244 mm or 192 mm wide. The boards are finished with the Uniclic® locking system for simple installation.

The boards are installed as a floating floor and sealed around the perimeter with a compressible PE foam rod which is then sealed with Hydroshield® sealant. This ensures that the floor is waterproof whilst still allowing for expansion and contraction.

Woodland supply accessories to aid in the installation:

- underlay to reduce sound transfer
- custom stair trims, and

Woodland Lifestyle Oasis & Oasis Wide Laminate Flooring PRODUCT TECHNICAL STATEMENT

Version 1.2. September 2023

• colour matched trims or aluminium C channels.

Sustainability

Unilin the manufacturer of Oasis Flooring is committed to sustainability. Their strategy focuses on the principles of the circular economy under the levels:

- Planet Home focusing on circular technologies, renewable energy and recycled materials.
- Your Home create healthy, comfortable and sustainable living environments, and
- Our Home create a positive, motivating and safe work environment.

Unilin supply an Environmental Product Declaration in respect of their direct pressure laminate flooring (cradle to grave). This is available on request.

Building code obligations

Code Clauses	Compliance pathway	Evidence
B1 (structure)	ALTERNATIVE SOLUTION	NZ does not have a cited standard in respect of laminate
B1.3.2, B1.3.3 (b, e, j, q)		flooring.
B2 (durability)	ALTERNATIVE SOLUTION	Oasis is manufactured to the applicable European standard with
B2.3.1(c), B2.3.2 (b)		respect to laminate flooring (EN 13329).
C3 (fire affecting areas beyond the fire source)	ACCEPTABLE SOLUTION	AWTA [04/05/2015] ISO 9239-1:2010, Test #15-001938.
C3.4(b)		Mean critical flux 5.6 kW/m².
D1 (access routes)	ACCEPTABLE SOLUTION	ISTS [20-10-2022] AS/NZS.4586:2004, Contract # 8006.
D1.3.3 (d)		Pendulum mean BPN 32.
E3 (internal moisture)	ALTERNATIVE SOLUTION	Oasis achieves less than the maximum moisture resistance
E3.3.3		requirements when tested to ISO 4760
E3.3.5		NZWTA [19/09/2022] ISO 4760:2022, #1433797.6.
E3.3.6		No evidence of water penetration through the joints.
F2 Hazardous Building Materials	ALTERNATIVE SOLUTION	Oasis is manufactured to EN 13329.
F2.3.1		Formaldehyde emissions < 0.01 ppm.

Woodland Lifestyle Oasis & Oasis Wide Laminate Flooring PRODUCT TECHNICAL STATEMENT

Version 1.2. September 2023

Scope of use and limitations

Scope	Limitation
Building work	
In conjunction with a substrate and primary structure that complies with the NZ Building Code, or where the primary structure is the equivalent stiffness to the framing provisions of NZS 3604:2011.	 Oasis flooring must be loose laid. The substrate must have a moisture content of <6 % at the time the floor is laid. For a concrete substrate and where the moisture content is > 6 %, a layer of 6 ml polyethylene may be installed. Oasis may not be laid over the following substrates: Carpet underlay or carpet Cushioned back vinyl Engineered or solid hardwood over concrete Rubber Cork PVC flooring Other free floating floors.
	 Substrates must not slope more than 25 mm per 1.83 m in any direction. Maximum deflection of the substrate must be < I/360. Substrates must be smooth and free of roughness with no changes in elevation. They must be 4.8 mm flat in a 3 m radius
For all building classified uses.	 Oasis is only for use in interior situations. Oasis in not intended for use in areas subject to high humidity or wet areas, it is suitable for use in areas subject to water splash.
For use as a flooring in an access route	Oasis flooring is not suitable for use in an access route where it is likely to become wet.
In connection with underfloor heating including in-slab piped water heating.	The substrate surface must not exceed 27° C.

Conditions of use

The system must be installed and maintained with all of Woodland Lifestyle requirements.

Additional information

For all design, installation and maintenance-related information, and for information supporting Woodland Lifestyle claims, refer to **www.woodlandlifestyle.com**

Oasis & Oasis wide laminate flooring is not subject to any ban issued under **S26 of the Building Act**.

Responsible person

In accordance with Regulation 8, as the responsible person, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is, therefore, to the best of my knowledge, correct.

Signed for and on behalf of Woodland Lifestyle:

Moses Hewetson

Moses Hewetson GENERAL MANAGER

28 February 2023